

OMNITRONIC EP-220NET Preamplifier met Internet Radio, DAB+ en Bluetooth

Model: 02910007079

Merk: CS



19" voorversterker met internetradio, DAB+, Bluetooth en IR afstandsbediening

Internetradio met DAB+ en FM-tuner, Bluetooth en UPnP/DLNA-ondersteuning
Breed scala aan streamingopties via WLAN, LAN-aansluiting en Bluetooth
Groot 2" TFT-kleurendisplay, eenvoudige bediening met jog-dial, equalizer-presets, slaaptimer en alarmfunctie
Toegang tot duizenden radiostations wereldwijd
Zenderscan op genre, zendernaam, locatie
4 stereo lijningangen (RCA) op het achterpaneel
3,5 mm AUX-ingang op het voorpaneel
1 combo-microfooningang met bedieningselementen voor volume, bas en hoge tonen op het voorpaneel
Audiobronkiezer
Regelaars voor volume, bas en hoge tonen
3 stereo master-uitgangen
Digitale en analoge audio-uitgangen (Toslink, coaxiaal, RCA)
(19") 48,3 cm rackmontage mogelijk

TECHNISCHE SPECIFICATIES

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 6 W

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Frequency range: 20 - 20,000 Hz

S/N ratio: >100 dB

THD: <0,1 % at 1 kHz

WiFi: Standard: IEEE 802.11 b/g/n

Security protocol: WEP/WPA/WPA2

Network connection: Protocol: Ethernet TCP/IP via RJ-45 (F) mounting version, 10/100 Mbit/s
Impedance: Input: 10 kOhm , unbal.
Input: 20 kOhm , bal.
Control: W-Lan; IR remote control
Bluetooth: Version: 4,2 + EDR
Audio player: FM-tuner + Internet radio + BT + DAB+
Housing color: Black
Display type: Multicolor TFT display
Tuner frequency range: FM 87-108 MHz, DAB(+) 174,928-239,200 MHz
Control elements: Power switch, source selector, level control, tone control, menu; navigation keys, encoder
Status LED: Power
Connections: Antenna via 1 x SMA (F) mounting version
Network connection via 1 x RJ-45 (F) mounting version
Input: antenna via 1 x Belling-Lee (F) mounting version
Input: line via 4 x stereo RCA
Input: AUX via 1 x 3.5 mm jack (stereo) mounting version
Input: Microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)
Output: line via 2 x 3-pin XLR (M) mounting version
Output: line via 2 x 6.3-mm-jack (bal.)
Output: line via 1 x stereo RCA
Output: optical via 1 x toslink
Output: co-axial (S/PDIF) via 1 x RCA (F) mounting version
Channels: Microphon chanal: 1 x mono via Combination socket (XLR/jack), channel control via Rotary dial, 2-band tone control EQ
Master output: stereo, channel control via Rotary dial, 2-band tone control EQ, source selector,
Music format: MP3, AAC/AAC+; FLAC
Frequency band: 2.4 GHz
Max. level: Input: line +20 dBu
Output: +22 dBu
Material: Metal
Housing design: Desktop console housing
(19") 48.3 cm rack installation possible
Dimensions: Width: 48,3 cm
Depth: 19 cm
Height: 4,4 cm
Weight: 2,00 kg
Remote control
Power supply: 3 V DC
Battery: 2 x Micro (AAA) (not included)

[Handleiding](#)